

SHIPPING INSTRUCTIONS

Send ad materials	Fax insertion orders to:
Women's Skiing Kristin Dann Production Department 353 Airport Road Oceanside, CA 92058 tel: (760) 722-7777 *Include magazine name and issue date.	Women's Skiing Amy Artzer 5720 Flatiron Parkway Boulder, CO 80301 tel: (303) 253-6420 fax: (303) 253-6377

ISSUE & CLOSING DATES

Women's Skiing is published once a year.

ISSUE	AD CLOSE	MATERIAL DUE	ON SALE
DECEMBER '08	09/08/08	09/12/08	11/18/08

UNITS AND SIZING

UNITS	NON-BLEED (w" x d")	BLEED (w" x d")	TRIM (w" x d")
Full Page	7 x 10	8-1/8 x 10-3/4	7-7/8 x 10-1/2
Spread	15 x 10	16 x 10-3/4	15-3/4 x 10-1/2

2008 ADVERTISING RATES

Four Color	1x
Full Page	\$17,705
Spread	\$34,650

SALES CONTACTS

boulder headquarters 5720 Flatiron Parkway Boulder, CO 80301 P) 303.253.6300 F) 303.253.6377	san francisco sales office 415 Jackson Street, 2nd Floor San Francisco, CA 94111 P) 415.218.3540 F) 415.351.4522
new york sales office 2 Park Avenue, 10th Floor New York, NY 10016 P) 212.779.5091 F) 212.779.5469	los angeles sales office 100 N. Sepulveda Blvd., Suite 1800 El Segundo, CA 90245 P) 310.227.8957 F) 310.414.1531
detroit sales office 39533 Woodward Avenue, Suite 330 Bloomfield Hills, MI 48304 P) 248.282.5546 F) 248.294.1761	chicago sales office 625 North Michigan Avenue, Suite 1270 Chicago, IL 60611 P) 312.252.2839 F) 312.573.1535

SPECS & MECHANICS

MAGAZINE TRIM SIZE: 7-7/8" x 10 1/2"

MECHANICAL REQUIREMENTS: Perfect Bound, Offset Printing; Jog to Foot — 1/8" Foot Trim

MAXIMUM DENSITY ACCEPTED: 300%

LINE SCREEN: 133

R.O.B. UNITS—SAFETY: live matter should be kept 1/4" from trim size

R.O.B. UNITS—TRIM: 1/8" all around

Material Specifications: SWOP standards apply.

File Formats Accepted: We will accept the following files: **PDFX1A** format is the preferred file format for file submission. When preparing **PDFX1A** files careful attention must be paid to ensure they are properly created and will reproduce correctly. Please see below for guidelines. Please call Rina Murray at (760) 722-7777 ext. 213, or email at rina.murray@bonniercorp.com if you have any other questions regarding material.

WE DO NOT ACCEPT APPLICATION FILES.

Media: The following are acceptable: Scitex UFS Optical, Mac formatted; CD-ROM, 100Mb Zip, 1.2Gb Jaz or DLT. Please label all media with issue date, agency name, contact name and phone number, advertiser, ad number, vendor name and contact. If you would like media returned, please include a return address.

Proofing: NO LASER PROOFS: We require one digital proof (Kodak Approval or Polaroid PolaProof preferred, Dupont Waterproof or Polaroid DryJet acceptable) generated from the digital file. **All proofs must bear Standard GATF Offset Color Bars/Exposure Scales and should be proofed to SWOP specifications.**

General Guidelines: Supply required screen ruling and dot shape and angle. Build pages to trim size and extend bleed beyond page edge. All elements must be placed at 100% of size. Use stylized fonts. Do not apply style attributes to basic fonts.

Do Not Use TrueType or Multiple Master Fonts.

- Include all printer and screen fonts, images/scans, logos/artwork.
- Do not nest EPS files in other EPS files.
- Pantone colors must be in CMYK mode. If you are planning on using a PMS, please contact Amy Artzer at (303) 253-6420, or email at amy.artzer@bonniercorp.com.
- All images/scans must be in CMYK mode.
- Font information should include manufacturer, font name and version.
- Four color solids should not exceed SWOP density of 300%.
- Supply one composite LW and CT file per page.
- Supply single pages on full page ads; on spread units, supply one continuous image file.
- Black text should be merged with the LW file.
- Supply hard copy proofs that match each supplied digital file.
- Proofs must be provided at 100% of size.
- 133 Line Screen required. Density should not exceed 300%.
- Rotation of Color: yellow, magenta, cyan, black
- If you have any additional questions, please contact Rina Murray at (760) 722-7777 ext. 213, or email at rina.murray@bonniercorp.com.